

GENERATOR 2800 W

- 5.8 HP engine pull cable starter
- Powerful and air cooled 4 stroke petrol engine with 212 cm³ displacement
- Max. 2800 W output power, 2500 W rated output
- Two 230 V connections
- Sturdy and robust steel frame with wheel kit and hinged handles
- Integrated overload protection, voltmeter and low oil warning



OPTIONAL ACCESSORIES

OIL ULTRA PERFORMANCE LONGLIFE SAE 5W-40 500 ml

Article number: 3906100701
Barcode: 4014915073512



Overload protection, voltmeter and low oil warning

SPECIFICATIONS - ENGINE

Model	Single-cylinder; 4 stroke petrol engine
Max. engine power	5.8 HP
Displacement	212 cc
Starter	Pull starter
Tank capacity	15 L
Fuel consumption 2/3 load	1.05 L/h
Fuel consumption at max. load	3.89 L/h

LOGISTICAL DATA

Weight net / gross	44.7 / 47 kg
Packaging dimensions	685 x 490 x 495 mm
Article number	5906226903
Barcode	4046664194668
40 HQ Container	375 pcs

SPECIFICATIONS - GENERATOR

Dimensions L x W x H	660 x 600 x 500 mm
Voltage control	AVR-System
Rated output / max. output	2500 / 2800 W
Socket	2 x 230 V~
AC frequency	50 Hz
Overload protection	Yes
Low oil warning	Yes
Voltmeter	Yes



EXAMPLES OF USE

Camping



Garden shed



Event



Construction site



Large tank capacity (15 litres)

Sturdy and robust steel frame

Easy to manoeuvre thanks to transport handles and large wheels

212 cc, 5.8 HP, 4-stroke petrol engine

PRODUCT DETAILS

2 x 230 V power outlet



Lasting



Robust



Powerful



Fuel-saving



Power pack



Transportable



AVR technology minimises voltage fluctuations and ensures consistent power from the generator

our SG3200x traditional manufacturers

